




Tassello per cava a T senza foro

Tassello per cava a T senza foro, in acciaio da bonifica, classe 8.8, DIN 508R.



DIN 508R



| Codice | € | D (mm) | A (mm) | B (mm) | C (mm) | Cava (mm) |
|------------|-----|--------|--------|--------|--------|-----------|
| C602270005 | --- | 7,7 | 13x13 | 10 | 6 | 8 |
| C602270010 | --- | 9,7 | 15x15 | 12 | 6 | 10 |
| C602270015 | --- | 11,7 | 18x18 | 14 | 7 | 12 |
| C602270020 | --- | 13,7 | 22x22 | 16 | 8 | 14 |
| C602270025 | --- | 15,7 | 25x25 | 18 | 9 | 16 |
| C602270030 | --- | 17,7 | 28x28 | 20 | 10 | 18 |
| C602270035 | --- | 19,7 | 32x32 | 24 | 12 | 20 |

| Codice | € | D (mm) | A (mm) | B (mm) | C (mm) | Cava (mm) |
|------------|-----|--------|--------|--------|--------|-----------|
| C602270040 | --- | 21,7 | 35x35 | 28 | 14 | 22 |
| C602270045 | --- | 23,7 | 40x40 | 32 | 16 | 24 |
| C602270050 | --- | 27,7 | 44x44 | 36 | 18 | 28 |
| C602270055 | --- | 31,6 | 50x50 | 40 | 20 | 32 |
| C602270060 | --- | 35,6 | 54x54 | 44 | 22 | 36 |
| C602270065 | --- | 41,6 | 65x65 | 52 | 26 | 42 |




Tassello per cava a T doppia lunghezza

Tassello per cava a T doppia lunghezza, in acciaio da bonifica, DIN 508L.



DIN 508



| Codice | € | d | a (mm) | Cava (mm) | e (mm) | l (mm) | h (mm) | k (mm) |
|------------|-----|-----|--------|-----------|--------|--------|--------|--------|
| C609030010 | --- | M6 | 7,7 | 8 | 13 | 26 | 10 | 6 |
| C609030020 | --- | M8 | 9,7 | 10 | 15 | 30 | 12 | 6 |
| C609030030 | --- | M10 | 11,7 | 12 | 18 | 36 | 14 | 7 |
| C609030040 | --- | M12 | 13,7 | 14 | 22 | 44 | 16 | 8 |

| Codice | € | d | a (mm) | Cava (mm) | e (mm) | l (mm) | h (mm) | k (mm) |
|------------|-----|-----|--------|-----------|--------|--------|--------|--------|
| C609030060 | --- | M16 | 17,7 | 18 | 28 | 56 | 20 | 10 |
| C609030080 | --- | M20 | 21,7 | 22 | 35 | 70 | 28 | 14 |
| C609030090 | --- | M24 | 27,7 | 28 | 44 | 88 | 36 | 18 |




Tassello per cava a T doppia lunghezza

Tassello per cava a T doppia lunghezza, in acciaio da bonifica, DIN 508L.



DIN 508




| Codice | € | Pz. | M | D (mm) | L (mm) | A (mm) | B (mm) | C (mm) | Cava (mm) |
|------------|-----|-----|----|--------|--------|--------|--------|--------|-----------|
| C602280005 | --- | 10 | 6 | 7,7 | 26 | 13 | 10 | 6 | 8 |
| C602280010 | --- | 10 | 8 | 9,7 | 30 | 15 | 12 | 6 | 10 |
| C602280015 | --- | 10 | 10 | 11,7 | 36 | 18 | 14 | 7 | 12 |
| C602280020 | --- | 10 | 12 | 13,7 | 44 | 22 | 16 | 8 | 14 |
| C602280025 | --- | 10 | 14 | 15,7 | 50 | 25 | 18 | 9 | 16 |
| C602280030 | --- | 10 | 16 | 17,7 | 56 | 28 | 20 | 10 | 18 |

| Codice | € | Pz. | M | D (mm) | L (mm) | A (mm) | B (mm) | C (mm) | Cava (mm) |
|------------|-----|-----|----|--------|--------|--------|--------|--------|-----------|
| C602280035 | --- | 1 | 18 | 19,7 | 64 | 32 | 24 | 12 | 20 |
| C602280040 | --- | 1 | 20 | 21,7 | 70 | 35 | 28 | 14 | 22 |
| C602280045 | --- | 1 | 22 | 23,7 | 80 | 40 | 32 | 16 | 24 |
| C602280050 | --- | 1 | 24 | 27,7 | 88 | 44 | 36 | 18 | 28 |
| C602280055 | --- | 1 | 27 | 31,6 | 100 | 50 | 40 | 20 | 32 |
| C602280060 | --- | 1 | 30 | 35,6 | 108 | 54 | 44 | 22 | 36 |



Tassello romboidale per cave T

Tassello romboidale per cave T, in acciaio da bonifica, Nr 510.



| Codice | € | M | D (mm) | A (mm) | B (mm) | C (mm) | Cava (mm) |
|------------|-----|----|--------|--------|--------|--------|-----------|
| C602300005 | --- | 10 | 11,7 | 18 | 14 | 7 | 12 |
| C602300010 | --- | 10 | 13,7 | 22 | 16 | 8 | 14 |
| C602300015 | --- | 10 | 17,7 | 28 | 20 | 10 | 18 |
| C602300020 | --- | 12 | 13,7 | 22 | 16 | 8 | 14 |
| C602300025 | --- | 14 | 15,7 | 25 | 18 | 9 | 16 |
| C602300030 | --- | 16 | 17,7 | 28 | 20 | 10 | 18 |
| C602300035 | --- | 16 | 19,7 | 32 | 24 | 12 | 20 |

| Codice | € | M | D (mm) | A (mm) | B (mm) | C (mm) | Cava (mm) |
|------------|-----|----|--------|--------|--------|--------|-----------|
| C602300040 | --- | 16 | 21,7 | 35 | 28 | 14 | 22 |
| C602300045 | --- | 16 | 27,7 | 44 | 36 | 18 | 28 |
| C602300050 | --- | 18 | 19,7 | 32 | 24 | 12 | 20 |
| C602300055 | --- | 20 | 21,7 | 35 | 28 | 14 | 22 |
| C602300060 | --- | 24 | 27,7 | 44 | 36 | 18 | 28 |
| C602300065 | --- | 30 | 35,6 | 54 | 44 | 22 | 36 |




Rondella normale piatta

Rondella normale piatta DIN 6340, in acciaio temprato.



DIN 6340



| Codice | € | Per filetto | Ø D1 (mm) | Ø D2 (mm) | s (mm) |
|------------|-----|-------------|-----------|-----------|--------|
| C609090005 | --- | M6 | 6,4 | 17 | 3 |
| C609090010 | --- | M8 | 8,4 | 23 | 4 |
| C609090020 | --- | M10 | 10,5 | 28 | 4 |
| C609090030 | --- | M12 | 13 | 35 | 5 |

| Codice | € | Per filetto | Ø D1 (mm) | Ø D2 (mm) | s (mm) |
|------------|-----|-------------|-----------|-----------|--------|
| C609090040 | --- | M14 | 15 | 40 | 5 |
| C609090050 | --- | M16 | 17 | 45 | 6 |
| C609090070 | --- | M20 | 21 | 50 | 6 |
| C609090090 | --- | M24 | 25 | 60 | 8 |